


# Kushion Walk No. 475

## Performance: BETTER



**Kushion Walk** is a super tough, abrasion resistant runner that combines modest comfort with solid construction. Its durable, textured surface guards against slip and fall injuries, while a knobbed bottom and **optional drainage slots** permit run-off and aeration. Kushion Walk's tough construction is ideal for grates and catwalks.

### Specs

**Uses** Mostly dry areas

**Compound** 100% Vinyl

**Durometer** 75 per ASTM D2240

**Coefficient of Friction** 1.03 Dry .81 Wet per ASTM F1677

**Tabor Abrasion** < 1% lost @ 1,000 cycles per Fed Std. 193


**Flammability** "A" Rating per MVSS 302

**Edging** Molded safety bevells

**Thickness** 3/8"

**Warranty** 1 year, conditional

**Colors** Black (BK), Black/Yellow (BYL)



### Stock Sizes

Part Number	Size
475.38x3x5	3' x 5'
475.38x2x60	2' x 60'
475.38x3x60	3' x 60'

Black is in stock


### Non-Stock Sizes

Part Number	Size
475.38x2Cut	2' Cut
475.38x3Cut	3' Cut

### Cut Sizes up to 60' in length

When ordering specify :  
Slotted (SLT) or Unslotted (UNS)

Specify Color:  
Black (BK), Black/Yellow (BYL)  
when ordering.



# Abrasive Coated Kushion Walk No. 480

## Performance: BETTER



**Abrasive Coated Kushion Walk** is an excellent option for slip resistance and comfort in hazardous industrial areas. An incredibly durable anti-fatigue runner, its improved GritWorks!® surface provides superb traction. Rugged enough for use on gratings, it is available with or without drainage slots.

### Specs

**Uses** Wet, slippery areas

**Compound** 100% Vinyl with gritted surface

**Durometer** 75 per ASTM D2240

**Coefficient of Friction** 1.10 Dry 1.10 Wet per ASTM F1677

**Tabor Abrasion** < 1% lost @ 1,000 cycles per Fed Std. 193


**Flammability** "A" Rating per MVSS 302

**Edging** Molded safety bevells

**Thickness** 3/8"

**Warranty** 1 year, conditional

**Color** Black (BK)



### Stock Sizes

Part Number	Size
480.38x2x60BK	2' x 60'
480.38x3x60BK	3' x 60'

### Non-Stock Sizes

Part Number	Size
480.38x2CutBK	2' Cut
480.38x3CutBK	3' Cut

### Cut Sizes up to 60' in length

When ordering specify :  
Slotted (SLT) or Unslotted (UNS)

