

## Super Erecta® and Super Adjustable Top-Track™ — 11.12

### Stationary End Unit Kits

Includes hardware necessary for connecting stationary end units to track. **One kit is required per single system. Shelves sold separately** — See pages 13 and 19. **86" (2185mm) posts included.**

Shelf Width (in.)	Shelf Width (mm)	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No. Chrome-Plated	List Price Each	Cat. No. Metroseal 3	List Price Each	Cat. No. Stainless Steel	List Price Each
18	457	11	4.9	<b>TTE18C</b>	485.00	<b>TTE18K3</b>	524.00	<b>TTE18S</b>	832.00
21	530	11.5	5.1	<b>TTE21C</b>	490.00	<b>TTE21K3</b>	533.00	<b>TTE21S</b>	837.00
24	610	12	5.4	<b>TTE24C</b>	496.00	<b>TTE24K3</b>	538.00	<b>TTE24S</b>	845.00




Super Erecta® Top-Track™

### Stationary Intermediate Unit Kits

Includes hardware necessary for connecting intermediate unit to track on both sides. **Shelves sold separately** — See pages 13 and 19. **86" (2185mm) posts included.**

Shelf Width (in.)	Shelf Width (mm)	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No. Chrome-Plated	List Price Each	Cat. No. Metroseal 3	List Price Each	Cat. No. Stainless Steel	List Price Each
18	457	7.5	3.3	<b>TTA18C</b>	283.00	<b>TTA18K3</b>	306.00	<b>TTA18S</b>	462.00
21	530	8	3.6	<b>TTA21C</b>	286.00	<b>TTA21K3</b>	309.00	<b>TTA21S</b>	467.00
24	610	8.5	3.8	<b>TTA24C</b>	290.00	<b>TTA24K3</b>	312.00	<b>TTA24S</b>	474.00

FRONT VIEW




### Track Sets

Includes necessary sections of track for assembling track runs of 6'-21' (1830-6405mm). For track sizes within the even 1-foot (305mm) increments, contact your Metro representative.

Length (feet)	Length (mm)	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No.	List Price Each
6	1828	40.5	18.2	<b>TTS6NA</b>	341.00
7	2135	47.5	21.3	<b>TTS7NA</b>	388.00
8	2440	56	25.2	<b>TTS8NA</b>	573.00
9	2743	62.5	28.1	<b>TTS9NA</b>	622.00
10	3048	69.5	31.2	<b>TTS10NA</b>	672.00
11	3353	76.5	34.4	<b>TTS11NA</b>	725.00
12	3657	83.5	37.5	<b>TTS12NA</b>	774.00
13	3962	92	41.4	<b>TTS13NA</b>	824.00
14	4267	98	44.1	<b>TTS14NA</b>	873.00
15	4572	106.5	47.9	<b>TTS15NA</b>	1,059.00
16	4877	113.5	51	<b>TTS16NA</b>	1,108.00
17	5182	121	54.4	<b>TTS17NA</b>	1,161.00
18	5486	128	51.6	<b>TTS18NA</b>	1,211.00
19	5791	135	60.7	<b>TTS19NA</b>	1,258.00
20	6096	142	63.9	<b>TTS20NA</b>	1,309.00
21	6400	149	67	<b>TTS21NA</b>	1,357.00

- A = Stationary End Units
- B = Stationary Intermediate Unit (Optional)
- C = Track Set
- D = Mobile Units
- E = Open Aisle

OVERHEAD VIEW



### Mobile Unit Kits

One kit required per mobile unit. Kit includes posts, casters/caster channels, donut bumpers, and roller bearing assemblies hardware and split sleeves. **Shelves sold separately** — See pages 13 and 19.

Shelf Width (in.)	Shelf Width (mm)	Overall Width (in.)	Overall Width (mm)	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)	Cat. No. Chrome-Plated	List Price Each	Cat. No. Metroseal 3	List Price Each	Cat. No. Stainless Steel	List Price Each
18	457	20 1/4	514	32	14.4	<b>TTM18C</b>	310.00	<b>TTM18K3</b>	527.00	<b>TTM18S</b>	693.00
21	530	23 1/4	590	33	14.8	<b>TTM21C</b>	318.00	<b>TTM21K3</b>	532.00	<b>TTM21S</b>	700.00
24	610	26 1/4	667	34	15.3	<b>TTM24C</b>	327.00	<b>TTM24K3</b>	538.00	<b>TTM24S</b>	707.00

#### Notes:

- Each stationary end and intermediate unit **must** have a minimum of four shelves. For all Super Adjustable applications, the top and bottom shelves must be non "quick adjust" Super Erecta shelves.
- The standard Deep Top-Track system requires the use of 86" (2185mm) posts (i.e., 86P, 86PK, or 86PS) on the stationary end and intermediate units. Shelves for the stationary end and intermediate units are sold separately.
- The mobile unit kit include special 74" (1880mm) posts with casters. Shelves for mobile units are sold separately.
- Recommended maximum load rating for a mobile unit is 900 lbs. (410kg). Floor should be level, smooth, and free from large cracks and raised obstacles.
- Under normal conditions, an aisle width of 30"-36" (760-914mm) is recommended. The storage of very large objects within the system, however, may require an aisle width larger than 36" (914mm).
- A stationary intermediate unit is required when track length exceeds 21 feet (6405mm). A stationary intermediate unit may be used at the discretion of the user when track lengths are less than 21 feet (6405mm).
- To accommodate bumpers, the actual size of a mobile unit is 2.5" (63.5mm) wider than the shelf width shown. For example, an 18" (457mm) wide unit is actually 20.5" (52mm).
- Add 1.5" (38mm) to nominal track length to accommodate track hardware.

Refer to pages 31-40 for a complete selection of Super Erecta Shelf accessories. For Top-Track accessories, see page 98.